

STAR 350/9 RAKE

FARMLINER®
VALUE - Since 1980

STAR 350/9 – ROTARY HAY RAKE

Fast clean raking of hay and silage for baling. The walking-beam tandem axle provides excellent tracking of ground contours. Adjustable curtain position for variable swath and overall working width

*Photo for illustration purposes.
Standard specifications may
not match those shown*



GEARBOX



36 TINE RAKE ROTOR



TRANSPORT



WINDROW

APPLICATIONS

Ideal for small scale hay and silage raking

SPECIFICATIONS

- Pivoting headstock
- PTO drive shaft with torque limiter
- Closed cam track gearbox in oil bath
- 9 arm / 36 tine rake rotor
- Curtain with adjustable position
- Removable arms for road transport
- Tandem wheels on walking beam
- Tyres 15x6
- 45hp minimum tractor horsepower

TECHNICAL DATA

Model	Working Width m	Transport Width m	Rotor Diameter m	 Minimum HP	 Kg	Tines
STAR 350	3.40-3.55	2.08	2.85	45	405	36



inlon
AGRI-MEC GROUP

Inlon Pty Ltd ABN 14 002 717 740
17 Catamaran Road, OURIMBAH NSW 2258
E. mail@inlon.com.au P. (02) 4360 4000
www.farmliner.com.au